



Commercial-grade USB computer-to-radio interface for controlling HF, VHF, UHF transceivers. Provides PTT, COR and transmit/receive audio through a single USB port.

Dry contacts for PTT, 600-ohm isolation transformers, and temperature-stabilized timebase (TCXO) for highly accurate tone signaling. RJ-45 connector for radio connection.

Includes CD-ROM with documentation and software drivers for Microsoft Windows™.

FEATURES:

- Integrated audio chipset
- TCXO timebase
- 600-ohm line transformers for TX/RX
- Use with local or IP remote software
- N.O. dry contact (relay) for PTT control
- COR input (carrier-operated relay)
- USB powered device
- MS Windows compatible

SPECIFICATIONS:

Environmental:

Amb. temp. range: -15 to +70 °C

Electrical:

Supply voltage: 4.5 – 5.5 VDC

Current draw (typ.) 100mA

PTT (Push-to-talk) control:

Control port: Integrated RS-232

PTT line: RTS

Connections:

Radio: RJ-45

Computer: USB (Type A)

TX/RX Audio:

ADC/DAC Resolution: 16 bits

THD+N: -74dB

SNR: 93dB

Frequency accuracy: 0.1% or better

Output level: 1.25Vrms max. (4.0Vpk-pk)

LED Indicators:

Ready

PTT

Input/Output Impedance:

600 Ω

BW Consultants / ComTekk

www.comtekk.com

Phone: (800) 708.2994

+1 (330) 967.0660